

Strut*Foot*



The **Strut*Foot***[™] Flat Roof Support System,
offering total flexibility for design, layout & installation.

- Channel framework provides strength & convenience for cable management installation
- Cross compatibility with all channel type brackets
- Fast & economical systems for mounting M&E services, Air Conditioning & Refrigeration on flat roofs
- Easy to install for individual products or complete installations
- No penetration of waterproof roof membrane
- Standard & bespoke configurations
- Anti-Vibration pads pre attached to feet
- Feet & blocks available separately



Strut*Foot* Support System - Technical Information

Part No	Product Description	Complete Leg Assembly Supplied	Sliding Arm Supplied	Side Rails (mm)	Sliding Arms (mm)	Product Weight (kg)	Max S.W.L (kg)
SF1302	Strut <i>Foot</i> 2	4	2	1000	1300	32	700
SF1304	Strut <i>Foot</i> 4	6	4	2000	1300	54	1050
SF1306	Strut <i>Foot</i> 6	8	6	3000	1300	78	1400
SF1308	Strut <i>Foot</i> 8	10	8	4000	1300	101	1750
SF1310	Strut <i>Foot</i> 10	12	10	5000	1300	124	2100
SF1312	Strut <i>Foot</i> 12	14	12	6000	1300	148	2450

Welding to ISO 9606-1

Galvanising to BS EN ISO 1461:1999

ISO 9001 Quality & ISO 14001 Environmental Certification Number 1753

Strut*Foot* Ltd, Alma Street, Wednesbury, West Midlands, WS10 0QB.

E-mail: sales@strutfoot.co.uk

Phone: 01922 650174

Fax: 01922 614969